

Specifications

| | WT5C/WTE5C* | WT5HP/WTE5HP** |
|-----------------------------------|--|---|
| Engine | | |
| Model | Honda GX120 | Honda GX160 |
| Power - Net Prime HP | 3.5 | 4.8 |
| Fuel Tank Gal. | 0.66 | 0.9 |
| Fuel Consumption GPH | 0.18 | 0.46 |
| Operating Speed RPM | 3,600 | 3,600 |
| Pump | | |
| Make | Multiquip | Multiquip |
| Model | QP2H (modified) | QP205SH (modified) |
| Type | 2" Centrifugal | 2" Centrifugal High Pressure |
| Max Flow GPM | 158 | 106 |
| Max Head Ft. | 115 | 230 |
| Water Tank | | |
| Type | Industrial Grade — Repairable | |
| Style | Rotomolded with 6 baffles | |
| Fill Port | 12" vented port | |
| Material | Polyethylene — 1/4" | |
| Fill Rate | Five minutes full fill @ full throttle | |
| Capacity Gal. | 525 | |
| Water Operations | | |
| Delivery Methods | Pressurized 1.5" and 2" left / 2" right; Pressurized rear spray nozzles; Three standard garden hose adapters | |
| Fill Methods | Municipal fire hydrant — QD; 1.5" and 2" Q/D cam and groove; Two standard garden hose adapters | |
| Trailer and Frame | | |
| Material | Formed steel channel frame | |
| Number of Axles | 2 | |
| Capacity — Axle Rating lb. | 3,500 | |
| Tires | ST205/75D 14" | |
| Certification | DOT | |
| Brakes | *Hydraulic actuated drum brakes (WT5C); Electric brakes (WTE5C) | **Hydraulic actuated drum brakes (WT5HP); Electric brakes (WTE5HP) |
| Hitch | 2-5/16" Ball Standard | |
| Jack Ratings lb. | 2,000 | |
| Hose Bin | Formed steel enclosure | |
| Hose Kit | 2" x 20 ft. Suction (HSQ220) 2" x 50 ft. Discharge (HDQ250) | 2" x 20 ft. Suction (HSQ220) 1" x 50 ft. 200 psi Hose Reel (WT5HR) |
| Size and Weight | | |
| Dimensions LxWxH in. | 146 x 68 x 80 | 146 x 68 x 80 |
| Trailer Weight DRY lb. | 1,530 | 1,630 |
| Trailer Weight WET lb. | 5,835 | 6,020 |

Accessories

Suction Hose (reinforced PVC) — (Male/Female NPT Thread Couplers)

| | | | |
|--------|------|--------|--------|
| HS1520 | 1.5" | 20 ft. | 90 psi |
| HS1525 | 1.5" | 25 ft. | 90 psi |
| HS220 | 2" | 20 ft. | 75 psi |
| HS225 | 2" | 25 ft. | 75 psi |

Suction Hose (reinforced PVC) — (Male & Female Cam & Groove Lock Couplers)

| | | | |
|---------|------|--------|--------|
| HSQ1520 | 1.5" | 20 ft. | 90 psi |
| HSQ220 | 2" | 20 ft. | 75 psi |
| HSQ225 | 2" | 25 ft. | 75 psi |

Discharge Hose (flat PVC) — NPT thread

| | | | |
|--------|------|--------|--------|
| HD1550 | 1.5" | 50 ft. | 75 psi |
| HD250 | 2" | 50 ft. | 75 psi |

Discharge Hose (flat PVC) — (Male & Female Cam & Groove Lock Couplers)

| | | | |
|---------|------|--------|--------|
| HDQ1550 | 1.5" | 50 ft. | 75 psi |
| HDQ250 | 2" | 50 ft. | 75 psi |

Discharge Hose — 2.5" Female Fire hydrant thread coupler, 2" x 25' Mill Hose and 2" Female Cam & Groove Lock Coupler

| | | |
|--------|--------|---------|
| HDFNST | 25 ft. | 200 psi |
|--------|--------|---------|

Male Cam & Groove Lock Couplers — Male quick-disconnect (Q/D) coupler, Female NPT Thread

| | | |
|-------|------|---------------------------------------|
| A150A | 1.5" | Male Q/D to 1.5" Female NPT thread |
| A200A | 2" | Male Q/D to 2" Female NPT thread |

Fire Fog Nozzle — 1.5" diameter, Female NPT thread

| | | |
|-----------|------|-----------------------|
| FIRENOZ15 | 1.5" | Adjustable fog nozzle |
|-----------|------|-----------------------|

Hose Reel Assembly

| | |
|-------|--|
| WT5HR | Includes industrial Reel Assembly, 1" x 50' 200 psi discharge hose, fire fog nozzle, all couplers and hardware to mate with the main manifold water control system |
|-------|--|

Hitches

| | |
|---------|--------------------------------------|
| 29228 | 2" ball, adjustable |
| 29369 | 2" pintle, adjustable |
| EE57033 | Bulldog, 2" ball, adjustable |
| EE56638 | Bulldog, 2-5/16" ball, adjustable |

Your Multiquip dealer is:

Connect with us on

